

# H25 Eco



## Electrically operated crimping machine

Our most economic electric power machine

- Hose capacity 3/16" - 1" (4 wire)
- Simple dial adjusted calibrator
- Simple die changing



Simple dial adjusted calibrator



Option of quick change rack




### Quick Change

Option of quick change rack for easy changing and storage of dies.



### Voltages

Available in a wide range of voltages (ask our sales team for specific voltage requirements)



### Delivery

Our distributors stock machines worldwide for fast delivery to you.

## Product features and specifications

Hose capacity	3/16" - 1" (4 wire)
Calibration	Simple dial adjusted calibrator
Max opening (without dies)	105 mm
Swaging force	1750kN
Max cycle time (O-C) / (C-O)	12 Sec / 7.5 Sec
Voltages 3 phase (Different voltages available)	220/240-380/440 50Hz OR 225/280-440/480 60Hz
Voltages 1 phase (Different voltages available)	220/240 50Hz
Additional die sets available	1 piece, Freon, PTFE & other
Packed Dimensions / Net Weight / Gross Weight (Data given without weights of extras)	790 x 600 x 900 mm / 123 Kgs / 142 Kgs



For die chart information please see the die charts at the back of this catalogue

For more information about this product, including spares, service and videos, visit our website

[www.hydralok.net](http://www.hydralok.net)