

H32 Range



Electronically controlled crimping machines

Our range of H32 power machines have various options of control and a wide range of optional extras to suit your needs.

- Hose capacity 3/16" - 1 1/4" (4wire) and 1 1/2" (2 wire with non standard dies)
- Choose between HydraTouch controller or simple dial adjusted calibrator
- Simple die changing



Touch screen controller



Simple dial adjusted calibrator



Option of foot pedal for hands-free operation (HydraTouch only)



Option of a camera for onscreen view of the back of the head for fast and more accurate crimping (HydraTouch Only)



Option of quick change system for easy changing of dies and useful storage



Option of gas struts for faster cycle times



Quick Change

Option of quick change rack for easy changing and storage of dies.



Voltages

Available in a wide range of voltages (ask our sales team for specific voltage requirements)



Memory Options

The Touch screen has the option of on board memory to save your crimp sizes, offsets, custom dies and more...

Product features and specifications

| | |
|--|---|
| Hose capacity | 3/16" - 1 1/4" R9R/4SP (4 wire) or 1 1/2" (2 wire with non standard dies) |
| Calibration | Touch screen controller or simple dial adjusted calibrator |
| Max opening (without dies) | 105 mm |
| Swaging force | 1750kN |
| Max cycle time (O-C) / (C-O) | 3 Sec / 7.5 Sec (without gas struts) 3 Sec / 4 Sec (with gas struts) |
| Voltages 3 phase (Different voltages available) | 220/240-380/440 50Hz OR 225/280-440/480 60Hz |
| Voltages 1 phase (Different voltages available) | 220/240 50Hz |
| Additional die sets available | 1 piece, Freon, PTFE & other |
| Packed Dimensions / Net Weight / Gross Weight (Data given without weights of extras) | 790 x 600 x 900 mm / 124 Kgs / 143 Kgs |



For die chart information please see the die charts at the back of this catalogue

For more information about this product, including spares, service and videos, visit our website

www.hydralok.net