

H50-46 Range



Electronically controlled crimping machines (Single taper)

Although the H50-46 range has the same crimping size as our H50 Range, the H50-46 range can crimp 6 wire hose.

- Hose capacity 3/16" - 2" (4 wire) and 1 1/2" (6 wire)
- Choose between HydraTouch controller or simple dial adjusted calibrator
- Single taper head with gas strut return



Touch screen controller



Simple dial adjusted calibrator



Option of foot pedal for hands-free operation (HydraTouch only)



Option of a camera for onscreen view of the back of the head for fast and more accurate crimping (HydraTouch Only)



Option of quick change system for easy changing of dies and useful storage



Gas strut return head features faster return times and reduced maintenance costs



Quick Change

Option of quick change rack for easy changing and storage of dies.



Voltages

Available in a wide range of voltages (ask our sales team for specific voltage requirements)



Memory Options

The Touch screen has the option of on board memory to save your crimp sizes, offsets, custom dies and more...

Product features and specifications

Hose capacity	3/16" - 2" R9R/4SP (4 wire) and 1 1/2" R13/4SH (6 wire)
Calibration	Touch screen controller or simple dial adjusted calibrator
Max opening (without dies)	123 mm
Swaging force	3195kN
Max cycle time (O-C) / (C-O)	7.5 Sec / 4.5 Sec
Voltages 3 phase (Different voltages available)	220/240-380/440 50Hz OR 225/280-440/480 60Hz
Voltages 1 phase (Different voltages available)	220/240 50Hz
Additional die sets available	1 piece, Freon, PTFE & other
Packed Dimensions / Net Weight / Gross Weight (Data given without weights of extras)	790 x 600 x 900 mm / 194 Kgs / 213 Kgs



For die chart information please see the die charts at the back of this catalogue

For more information about this product, including spares, service and videos, visit our website

www.hydralok.net