

H50 Range



Electronically controlled crimping machines

Our range of H50 power machines have various options of control and a wide range optional extras to suit what you need.

- Hose capacity 3/16" - 2" (4 wire)
- Choose between HydraTouch controller or simple dial adjusted calibrator
- Simple die changing



Touch screen controller



Simple dial adjusted calibrator



Option of foot pedal for hands-free operation (HydraTouch only)



Option of a camera for onscreen view of the back of the head for fast and more accurate crimping (HydraTouch Only)



Option of quick change system for easy changing of dies and useful storage



The HydraTouch version of the H50 features Gas strut return head with faster return times and reduced maintenance costs



Quick Change

Option of quick change rack for easy changing and storage of dies.



Voltages

Available in a wide range of voltages (ask our sales team for specific voltage requirements)



Memory Options

The Touch screen has the option of on board memory to save your crimp sizes, offsets, custom dies and more...

Product features and specifications

Hose capacity	3/16" - 2" R9R/4SP (4 wire)
Calibration	Touch screen controller or simple dial adjusted calibrator
Max opening (without dies)	120 mm
Swaging force	2509kN
Max cycle time (O-C) / (C-O)	4 Sec / 8 Sec (without gas struts) 4 Sec / 5 Sec (with gas struts)
Voltages 3 phase (Different voltages available)	220/240-380/440 50Hz OR 225/280-440/480 60Hz
Voltages 1 phase (Different voltages available)	220/240 50Hz
Additional die sets available	1 piece, Freon, PTFE & other
Packed Dimensions / Net Weight / Gross Weight (Data given without weights of extras)	790 x 600 x 900 mm / 159 Kgs / 178 Kgs



For die chart information please see the die charts at the back of this catalogue

For more information about this product, including spares, service and videos, visit our website

www.hydralok.net